

LAUBE

METAL OXIDE VARISTORS

**(K SERIES)
(Low Capacitance)**

7MM DIAMETER

K Series (Low Capacitance)

| Part No. | Maximum Allowable Voltage | | Energy 10/1000 μ S (J) | Withstanding Surge Current | | Rated Wattage (W) | Varistor Voltage at 1mA (V) | Maximum Clamping Voltage at 10A (V) | Typical Capacitance 1kHz (pF) |
|-----------|---------------------------|-----------|-------------------------------------|----------------------------|---------|-------------------------|-----------------------------------|--|-------------------------------------|
| | ACrms (V) | DC (V) | | 1 time | 2 times | | | | |
| | | | | (A) | | | | | |
| 151KD07-K | 95 | 125 | 16.8 | 1200 | 600 | 0.25 | 150(135-165) | 250 | 250 |
| 121KD07-K | 75 | 100 | 14 | | | | 120(108-132) | 200 | 350 |
| 101KD07-K | 60 | 85 | 11.6 | | | | 100(90-110) | 165 | 450 |
| 820KD07-K | 50 | 65 | 9.8 | | | | 82(74-90) | 135 | 550 |

The general characteristics of above items meet to Standard series

Specifications are subject to change without notice, please contact our sales office before ordering.